

DATA SHEET

PYROGUARD RAPIDE EW60

PYROGUARD RAPIDE EW60, 11MM is perfect for indoor and outdoor use. It's large sheet size and double sided fire resistance can be cut to size making it a cost effective solution.

TECHNICAL INFORMATION

Fire Resistance (En 13501-2)	EW60
Impact Resistance (EN 12600)	2(B)2
Light Transmission	88%
Sound reduction	35 dB
U Value	5.5 W/m ² K
UV Stability (EN ISO 12543-4)	Yes
Nominal Thickness	11mm
Thickness Tolerance	-1 / +1.4 mm
Weight	27 kg per m ²
Temperature Range	-20 / +100 °C
Sheet Size	1580 x 2780 mm

KEY FEATURES


60/0


- ☒ EW60 Impact
- ☒ 2(B)2 impact classification
- ☒ Interior and exterior use
- ☒ Double sided fire resistance
- ☒ UV stability
- ☒ Steel & timber applications

SUITABLE APPLICATION

- ☒ Can be used in fire tested timber, steel and aluminium systems.

STORAGE AND HANDLING

-  Must be handled with care during transportation, storage, inspection and installation. Store in a dry place.

 If you need help, please email: technical@fireglassuk.com

 CERTIFIRE REF: CF257



FIRE RESISTANT GLASS MUST ONLY BE USED AS PART OF AN APPROPRIATELY APPROVED GLAZING SYSTEM.

PLEASE MAKE SURE THE GLASS YOU USE IS SUITABLE FOR THE APPLICATION. IF IN DOUBT SPEAK TO OUR TECHNICAL DEPARTMENT: [TECHNICAL@FIREGLASSUK.COM](mailto:technical@fireglassuk.com)



Glass and Glazing Federation

